



Fabrication Materials: Stainless Steel 304L with electro-polished finish  
 Includes built in retractable casters. When weight is applied on first step the casters retract inside and the ladder sits on the 4 "mooncasters" which have a white nylon non marking insert to protect the floor.

Always use the right type of step stool for the job.  
 Always check that your step stool is in good working condition prior to use.  
 Never over-reach: keep your body centered on the step stool at all times.  
 Never have more than one person on a step stool at one time.  
 Don't overload the step stool; remember that the maximum load (120kg) includes any equipment that you need to have with you.

Estimation total weight <b>37 kg</b>	VARIATION IN DIMENSIONS WITHOUT TOLERANCE IND. DIN 7168		<b>PalbamClass</b> EN HAROD IHUD	EUROPE PROJ
	BREAK EDGES 0.3x45	STATUS MEDIUM		REV B
ALL RIGHTS STRICTLY RESERVED USE. REPRODUCTION OR ISSUE TO THIRD PARTY IN ANY FORM WHATEVER IS NOT PERMITTED UNLESS AUTHORIZED IN WRITING BY THE PROPRIETOR PalbamClass IL-18960 EN-HAROD IHUD-ISRAEL.	INNER RADIUS	SURF. ROUGH. PER ISO 1302	Step Ladder 4	
	DATE 13/02/2007	NAME Alexey	CATALOG # 4-STLD	
	DESIG		DWG. No.	PCCL0803-000
	APPR		SHEET 1 / 1	
CONTROLLED COPIES OF THIS DOCUMENT HAVE A RED ISSUE DATE STAMP, THESE COPIES WILL BE UPDATED BY PALBAM CLASS INFORMATION SYSTEM. ANY OTHER COPY IS NOT CONTROLLED AND THEREFORE NOT UPDATED. PLEASE CHECK WITH INFORMATION SYSTEM FOR VALIDITY OF DOCUMENT.				